

Section 165-030 Lot Frontage and Access

1. No building to be used in whole or part as a dwelling in a residential zone shall be erected on any lot, except as noted in this section, unless the lot abuts a street, as defined in these regulations, and has safe and direct access to the street by its own private driveway. The entire driveway must be located on the lot that it serves, except as noted in this section.
2. Rear Lots: No building to be used in whole or in part as a dwelling in a residential zone shall be erected on any rear lot, except as noted in this section, unless this rear lot has its own separate and individual unobstructed right-of-way, which is everywhere not less than 20 feet in width connecting to a street adequate to accommodate fire apparatus or other emergency equipment. The lot line from which the right-of-access leads shall be considered the front line of the rear lot.

Each rear lot created after the enactment of this section shall also comply with the following: The front lot line of a rear lot must conform to the frontage length as defined in these regulations and as noted in the Lot Area table found in Section 020-010. The twenty foot (20') accessway width shall be included for purposes of meeting the frontage requirement. Such rear lot shall conform to all the requirements prescribed in the zone in which it is located. (*Effective: September 15, 2006*)

3. Common Driveway: A common driveway is defined as a privately owned and maintained driveway located on a strip of land which is everywhere not less than 20 feet in width, connecting to a street serving at least two (2) lots, but no more than six (6) lots. All common driveways must be designed and built pursuant to the design standards and construction standards set forth in the subdivision regulations which standards are incorporated and made part of these regulations.
4. Reduced Frontage Exception: Each lot created after the enactment of this section shall meet the minimum frontage for the zoning district within which it is located, except when such lot or lots will have frontage partly or totally on a cul-de-sac or road curve, such frontage shall be not less than one hundred feet (100') when measured along the arc of the curve or circle, or except when such lot is a rear lot as defined by these regulations. A lot allowed a reduced frontage in accordance with this regulation must have an average width equal to at least the length of the required lot frontage for the zone. (*Effective: September 15, 2006*)